

Rockfon® Cinema Black™

FEATURES & BENEFITS

APPLICATIONS

- Factory painted glass scrim
- Good sound absorption (NRC = 0.85 0.95)
- High fire performance
- Lightweight panel, easy to carry and install
- Available in square lay-in

- Cinema
- Auditorium



LEED[®] V4 HIGHLIGHTS

	Materials and Resources (MR)	
	Construction & Demolition Waste Management Planning	\checkmark
	Interiors Life Cycle Impact Reduction - Designed for Flexibility	
	Building Product Disclosure and Optimization - Environmental Product Declarations	\checkmark
	Building Product Disclosure and Optimization - Sourcing of Raw Materials	\checkmark
	Building Product Disclosure and Optimization - Material Ingredients	\checkmark
	Construction and Demolition Waste Management	\checkmark
	Indoor Environmental Quality (EQ)	
	Low-Emitting Materials	\checkmark
	Interior Lighting	\checkmark
	Acoustic Performance	\checkmark
K	ECYCLED CONTENT: UP TO 42%	



CREATE AND PROTECT®

Rockfon® Cinema Black™

							-2		JA,		60	
Edge designat	ion	ltem number	Modular size (nominal)	lbs/ sqft	sqft/ carton	NRC	CAC	AC	Fire Class	Light Reflectance	Sag resistance (relative humidity)	LOW VOC
	SQ	1200	2′ x 2′ x 5/8″	0.38	112	0.85	-	-	А	0.04	UP TO 100%	\checkmark
Square Lay In	SQ	1201	2' x 4' x 5/8"	0.38	112	0.85	-	-	А	0.04	UP TO 100%	\checkmark
	SQ	1210	2′ x 2′ x 1″	0.45	64	0.95	-	-	А	0.04	UP TO 100%	\checkmark
	SQ	1211	2'x 4'x 1"	0.45	64	0.95	-	-	А	0.04	UP TO 100%	\checkmark

MATERIAL

Stone wool (Mineral Wool) ceiling tiles with factory painted glass scrim surface

ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



FIRE PERFORMANCE:

Surface burning characteristics: UL723 (ASTM E84) Flame Spread Index: 5 Smoke Developed Index (UL Labeled): 0 CAN/ULC S102 Flame Spread Index: 15 Smoke Developed Index: 5



VOC/FORMALDEHYDE EMISSIONS

All Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen.



CLEANING

Vacuum



ENVIRONMENT Fully recyclable



THERMAL INSULATION

R Value (BTU Units): 2.2 - 3.5 RSI Value (Watts Units): 0.39 - 0.62



WARRANTY INFORMATION: 30-Year Limited Product Warranty. See www.rockfon.com

HYGIENE

Stone wool provides no sustenance to microorganisms