

# Rockfon<sup>®</sup> Pacific<sup>™</sup>

Datasheet



**Sounds Beautiful**

# Rockfon® Pacific™





- Economical tile with standard surface
- Class B sound absorption with lightweight 12mm thickness
- Basic range of tile dimensions in semi-concealed and visible grid options
- Easy to clean with a vacuum

## Product Description

- Stone wool tile
- Visible side: Nuanced white painted fleece
- Rear Side: back fleece

## Application Areas

- Office
- Retail

Edge detail	Module size (mm)	Approximate weight (kg/m <sup>2</sup> )	Recommended installation System
 A15	600 x 600 x 12	1,6	Chicago Metallic™ T15 4070
	1200 x 600 x 12	1,6	Chicago Metallic™ T15 4070
 A24	600 x 600 x 12	1,6	Chicago Metallic™ T24 3220
		1,6	Chicago Metallic™ T24 1920
	1200 x 600 x 12	1,6	Chicago Metallic™ T24 3220
		1,6	Chicago Metallic™ T24 1920
 E15	600 x 600 x 12	1,9	Chicago Metallic™ T15 4070
 E24	600 x 600 x 12	1,9	Chicago Metallic™ T24 3220
		1,9	Chicago Metallic™ T24 1920



## Performance



**Sound absorption**  
 $\alpha_{0.5}$ : 0.80 (Class B)



Thickness (mm) /  
 Suspension (incl. tile - mm)

	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	$\alpha_w$	Absorption class	NRC
12 / 200	0.40	0.80	0.85	0.75	0.80	0.80	0.80	B	0.80



**Reaction to fire**  
 A1



**Humidity and sag resistance**  
 Up to 100% RH.  
 No visible deflection in high humidity



**Cleaning**  
 - Vacuum



**Hygiene**  
 Stone wool provides no sustenance to microorganisms



**Environment**  
 Fully recyclable stone wool  
 The recycled content of Rockfon products is between 29% and 64% according to ISO 14021.



**Carbon footprint**  
 1.96 - 2.11 kg of CO2 eq.  
 (cradle to gate based on EPD)



**Indoor environment**  
 A selection of Rockfon products have been awarded the Finnish M1 emission classification for building materials and the Danish Indoor Climate Label for low emission products



Rockfon® is a registered trademark  
of the ROCKWOOL Group.

06.2021 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

## Sounds Beautiful

### Rockfon Singapore

ROCKWOOL Building Materials  
(Singapore) Pte Ltd.  
No. 7, Tuas Avenue 1  
Jurong Town,  
Singapore 639492  
Tel: (+65) 6861 4722  
Fax: (+65) 6862 3533  
E-mail: [enquiry@rockfon.com](mailto:enquiry@rockfon.com)  
[www.rockfon.asia](http://www.rockfon.asia)

### Rockfon Hong Kong

ROCKWOOL Building Materials  
(Hong Kong) Ltd.  
Unit 301-2, 3/F, Koon Wah Building,  
No.2 Yuen Shun Circuit,  
Yuen Chau Kok, Shatin,  
N.T., Hong Kong  
Tel: (+852) 2576-6117  
Mobile: (+852) 9161-7924  
E-mail: [enquiry@rockfon.com](mailto:enquiry@rockfon.com)  
[www.rockfon.asia](http://www.rockfon.asia)

### Rockfon

ROCKWOOL Middle East FZE  
Office 139, Building 6WB, DAFZA  
P. O. Box 293585, Dubai, UAE  
  
Tel: +971-4-214-6280  
E-mail: [rockfonme@rockfon.com](mailto:rockfonme@rockfon.com)  
[ae.rockfon.com](http://ae.rockfon.com)

### Rockfon

ROCKWOOL France S.A.S.  
111, rue du Château des Rentiers  
75013 Paris  
  
Tel: +33 1 40 77 82 82  
Fax.: +33 1 45 86 77 90  
E-mail: [info@rockfon.fr](mailto:info@rockfon.fr)  
[www.rockfon.fr](http://www.rockfon.fr)

